

## Transporte de tambor

ref.:	C	L	H	K	peso	rodas
<b>TM-5</b>	570	1294	1017	300	16,8	- 2 fixas: RM-40 - 1 girat. de 4"

### Características gerais

- › Rodas maciças



ref.:	C	L	H	K	peso	rodas
<b>TM-32</b>	675	513	1321	200	10,8	RM-39

### Características gerais

- › Rodas maciças



ref.:	C	L	H	K	peso	rodas
<b>TM-82</b>	620	620	155	300	7,3	4 giratórias de 3"

### Características gerais

- › Rodas maciças



## Entornador de tambor

ref.:	C	L	H	K	peso	rodas
<b>TM-6</b>	611	855	553	300	9	- 2 fixas de 4" - 1 gir. de 3"

### Características gerais

- › Rodas maciças



ref.:	C	L	H	K	peso	rodas
<b>TM-96</b>	760	575	1316	300	19,7	RM-6

### Características gerais

- › Transporta e entorna o tambor
- › Rodas maciças



## Transporte de botijão

ref.:	C	L	H	K	peso	rodas
<b>TM-30</b>	570	602	1430	300	15,3	RM-8A

### Características gerais

- › Transporta 3 botijões de 13 kg ou 1 botijão de 45 kg
- › Rodas pneumáticas



## Carros gari

ref.:	C	L	H	K	peso	rodas
<b>TM-73</b>	770	883	729	88L	17	RM-40

### Características gerais

- › Rodas maciças



ref.:	C	L	H	K	peso	rodas
<b>TM-74</b>	815	944	755	88L	18	RM-147

### Características gerais

- › Rodas pneumáticas



## Transporte de pneus

ref.:	C	L	H	peso	rodas
<b>TM-103</b>	650/1100	400	910	7,2	- 2 fixas de 3" - 4 girat. de 3" (uma com freio)

### Características gerais

- › Comprimento útil (min / max): 600 mm / 1050 mm
- › Comprimento regulável

